

SIGLENT Introduces New 16 V/8 A DC Power Supply - SPD1168X

May 28, 2018

ShenZhen, May 28, 2018 SIGLENT Technologies has announced the release of its new 16 V/8 A DC power supply, the SPD1168X

Highlights:

- **Single Output: 0 - 16 V / 8 A**
- **High-Resolution: 1mV/1mA**
- **Low Ripple: $\leq 350\mu\text{Vrms}/3\text{mVpp}$**

Small in Size Big on Features

SPD1168X Series Programmable DC Power Supplies

- Single Output: 0 - 16 V / 8 A
- Low Ripple; Faster Response
- Four-Wire Compensation (Sense) Function
- Resolution of up to 1 mV / 1 mA




More Resolution and Accuracy

The SPD1168X programmable DC power supply includes set-point resolution of up to 1mV / 1mA and excellent setting and readback accuracy. Users can generate even very small voltage or current changes, while maintaining a well-regulated DC output across varying loads.


More DUT Safety

A lab power supply must produce a predictable and controlled output. This is necessary in order to protect the device being tested – the load. The SPD1168X power supply avoids overshoot, thus protecting the user's important device under test.




More Output Purity

The SPD1168X's ripple and noise is a low $\leq 350\mu\text{V}_{\text{rms}}$ / 3mV_{pp} , providing users with a cleaner power supply test environment.



Faster Response

The fast transient response time of the SPD1168X programmable DC power supply is less than $50\mu\text{s}$, thus, allowing the output voltage to quickly return to the set value when the DUT load undergoes a sudden change. Changing loads often happen in devices such as mobile phones, WiFi, wireless sensors, etc. The load can change faster than the transient response capability of other power supplies and can result in the supply voltage failing to quickly reach its set value, even in a testing environment, this fast load change can automatically cause the device to shut down or start repeatedly. The SPD1168X can be the perfect solution to this problem.



Smarter

Unlike some other traditional power supplies, the SPD1168X includes a four-wire compensation (Sense) function. The four-wire Sense mode compensates for potential voltage drops at the load due to the power supply leads causing an IR drop at higher currents. Using remote sensing, the SPD1168X can compensate for up to a 1 Volt loss in the output leads. Thus ensuring that the voltage supplied to the DUT is the same voltage that the power supply is set to. For added safety, if the compensation exceeds 1V, the power supply will automatically shut off its output so as to more intelligently protect the user's device under test.

With the SPD1168X's clean front-panel layout and compact body size, it requires minimal test bench space. And it is light enough to grab and go.

More details, please click [here](#)



North American Headquarters

SIGLENT Technologies America, Inc
6557 Cochran Rd Solon, Ohio 44139
Tel: 440-398-5800
Toll Free: 877-515-5551
Fax: 440-399-1211
info@siglent.com
www.siglentamerica.com/

European Sales Offices

SIGLENT TECHNOLOGIES EUROPE GmbH
Staetzlinger Str. 70
86165 Augsburg, Germany
Tel: +49(0)-821-666 0 111 0
Fax: +49(0)-821-666 0 111 22
info-eu@siglent.com
www.siglenteu.com

Asian Headquarters

SIGLENT TECHNOLOGIES CO., LTD.
Blog No.4 & No.5, Antongda Industrial Zone,
3rd Liuxian Road, Bao'an District,
Shenzhen, 518101, China.
Tel: + 86 755 3661 5186
Fax: + 86 755 3359 1582
sales@siglent.com
www.siglent.com/ens