

Measurement Data Depth SDS2000X vs. SDS1/2 X-E

December 18, 2018

One of the more powerful features of digital oscilloscopes is the automatic measurement function.

Most modern scopes allow you to measure 20 or 30 separate waveform parameters including rise/fall time, phase difference, peak-to-peak voltage, and more.

Some functions can actually measure large data sets to provide a “running average” of the measurement over a long time period.

The SIGLENT SDS X-E series utilizes all of the data in memory for measurements, including RMS. This can be up-to 14 Mpts.

In comparison, the SDS2X series 14 kpts due to resource limitations.



North American Headquarters

SIGLENT Technologies America, Inc
6557 Cochran Rd Solon, Ohio 44139
Tel: 440-398-5800
Toll Free: 877-515-5551
Fax: 440-399-1211
info@siglent.com
www.siglentamerica.com/

European Sales Offices

SIGLENT TECHNOLOGIES EUROPE GmbH
Staetzlinger Str. 70
86165 Augsburg, Germany
Tel: +49(0)-821-666 0 111 0
Fax: +49(0)-821-666 0 111 22
info-eu@siglent.com
www.siglenteu.com

Asian Headquarters

SIGLENT TECHNOLOGIES CO., LTD.
Blog No.4 & No.5, Antongda Industrial Zone,
3rd Liuxian Road, Bao'an District,
Shenzhen, 518101, China.
Tel: + 86 755 3661 5186
Fax: + 86 755 3359 1582
sales@siglent.com
www.siglent.com/ens