

SSA3000X External Reference Clock Recommendations

October 25, 2017

The external clock input of the SSA3000X series of spectrum analyzers has the following specifications:

External Clock Input: 1-5 Vp, 10 MHz, edge-detected, sine (preferred).

Square waves containing a 10 MHz rising edge can work, but harmonics may affect performance.

Clock Output: Approximately 1 Vp (0-1 V), 10 MHz sine wave.

North American Headquarters

SIGLENT Technologies NA
6557 Cochran Rd Solon, Ohio 44139
Tel: 440-398-5800
Toll Free: 877-515-5551
Fax: 440-399-1211
info@siglent.com
www.siglentamerica.com/

European Sales Offices

SIGLENT TECHNOLOGIES GERMANY GmbH
Liebigstrasse 2-20, Gebaeude 14,
22113 Hamburg Germany
Tel: +49(0)40-819-95946
Fax: +49(0)40-819-95947
info-eu@siglent.com
www.siglenteu.com

Asian Headquarters

SIGLENT TECHNOLOGIES CO., LTD.
Blog No.4 & No.5, Antongda Industrial Zone,
3rd Liuxian Road, Bao'an District,
Shenzhen, 518101, China.
Tel: + 86 755 3661 5186
Fax: + 86 755 3359 1582
sales@siglent.com
www.siglent.com/ens